

TC-320

Cost-effective Business

Two-way Radio

HYT's TC-320 is unique for its compact and professional design, as well as its superb sound quality. Its strong casing prevents damage against drops of up to five feet and its high capacity battery provides over 9 hours of reliable operation. This radio enables businesses to enjoy dependable communications at an extremely low cost. It is the perfect solution for hotels, retail stores, and schools.







Superb Sound Quality Stylish, Compact, & Light Weight Double Injection Molding & Anti-Skid Design Battery Save & Low Battery Alert Chargeable & Programmable through Mini-USB



www.hytamerica.com

TC-320

Technical Highlights

- Wide Communication Range
 2W output power can realize wide communication range of up to 6 miles.
- Durable Casing
 Compact and durable design that is strong enough to withstand a 1.5 M drop.
- Long Battery Life

1700mAh high capacity Li-Ion battery can secure a battery life of over 9 hrs.

Sleek & Light-Weight


With its ergonomic design, this slim and compact radio can enhance user comfort, while maintaining a professional and fashionable appearance.

- Double Injection molding and Grip Design
 The combination of double injection molding and grip technology brings users a comfortable and convenient operation experience.
- Chargeable & Programmable through Mini-USB Interface
 Plug this radio directly into the outlet from the radio or from the optional charger.

Main Features-

- Audio Compandor
- Scrambler (Compatible with TC-320 & TC-518)
- VOX Earpiece
- Battery Strength Indicator
- High/Low Power Switchable
- Programmable 25 KHz /12.5 KHz Channel Spacing
- Monitor
- CTCSS/CDCSS and Squelch Tail Elimination
- Channel Scan
- Auto Battery Save
- Low Battery Alert
- Busy Channel Lockout(BCL)
- Time-out-timer (TOT)
- PC Programmable
- Wired Clone

Accessories



•Note: Pictures are for reference only. Image may vary from actual product. Product function shall remain the same

Cost-effective Business Two-way Radio

General -

Frequency Range (MHz)	UHF: 400-420*; 450-470
Channel Capacity	16
Channel Spacing (KHz)	25/12.5
PLL Channel Stepping (kHz)	5 kHz, 6.25 kHz
Operating Voltage (V)	3.7
RF Power Output (w)	2 Watts
Battery	1700 mAh (Li-Ion)
Battery Life (5-5-90 duty cycle)	Over 9 Hours
Frequency Stability (ppm)	±5
Operating Temperature (F°)	-4° ~ +131°
Antenna Impedance (Ù)	50
Dimensions	3.94 in. x 1.89 in. x 1.06 in.
Weight (with antenna & battery)	4.76 oz.

Frequencies Marked with an Asterisk () are for Export Only

All specifications are tested according to TIA/EIA-603, and subject to change without notice due to continuous development.

Recommended Applications

- Retail Stores
- Hotels & Restaurants
- Supermarkets
- Education

- Office Environments
- Hospitals
 - Car Dealerships
 - Property Management









Your Local Dealer

FCC Approved Band: (450-470MHz) FCC ID Number R74TC-320U2





HYT America, Inc. 320 International Parkway, Sunrise, Florida 33325 Tel: 800-845-1230 Fax: 954-846-1672 Web: http://www.hytamerica.com

SHENZHEN HYT SCIENCE & TECHNOLOGY CO., LTD.

HYT "is the registered trademark of Shenkhen HYT Science & Technology Co., Lid. © 2007 HYT.Co.,Ltd. All Rights Reserved. HYT relains the right to change the product design and specifications. Should any printing mistake occur, HYT will not bear relevant responsibility. Some slight differences between real product and the product indicated by the printing materials may occur.